

AccuPort™



RFID Technology, Advanced Storeroom Control

The AccuPort utilizes passive RFID technology and CribMaster Inventory Management software to effectively manage any type of inventory in a centrally located tool crib or storeroom environment. This secure RFID portal system streamlines operations by eliminating manual logs and barcode scanning. Transactions are recorded in real time, providing a high level of accuracy to reduce stockouts and gain better control of your indirect materials.

- Minimize staffing requirements
- Improve inventory accuracy
- 24/7 secure access for authorized employees
- · Automatically track inventory in and out of a secured area



Suggested Inventory Types

Offering complete flexibility, the AccuPort is an ideal solution for managing all types of inventory items including durables and high-use consumables such as:

- Hand tools
- Power tools
- PPF
- · Singularly tagged kits
- Spare parts

Accessories

- Near-field RFID scanner for tool tagging assignments
- RFID shield panels to contain RFID signals to the tool crib
- Additional exit badge reader for enhanced user access
- AccuCheck to optimize RFID tag performance
- Industrial RFID printers for printing and encoding disposable RFID labels


RFID Tag Solutions

AccuPort RFID technology employs passive traceable tags that are adhered to various types of inventory. RFID tags come in a variety of durability, shapes, and sizes and are used based on the tool's shape, size, and surface material.

Tag Type	Item Type
Metal mount tag	Durable items
Non-metal mount tag	Consumables and durables
Cord mount tag	Corded power tools and cables
Hang tag	Consumables and durables
Smart label	Consumables

AccuPort Specs

Exterior Dimensions			
Height	87.5 in	222.25 cm	
Width	66.63 in	169.24 cm	
Depth	24.5 in	62.23 cm	
Weight			
Main	1050 lbs	476 kg	
Crating Dimensions			
Height	95 in	241.3 cm	
Width	76 in	193.04 cm	
Depth	34 in	86.36 cm	
Power Requirements			
Amps	2	1 (EU)	
Voltage	120	230 (EU)	
Operating Environment			
Temperature	32°F to 95°F	0°C to 35°C	
Humidity	20% to 85% (no co	ndensation)	
Technical Info			
CE Compliant			
Windows OS			





CribMaster Global Headquarters 1955 West Oak Circle Marietta, GA 30062

Toll Free // 1.877.960.0602 www.cribmaster.com